

# KETKO magnus™

Electric Storage Water Heater

6 / 10 / 15 / 25 / 35 / 50 Litres

230Volts / 1 Phase 3 / 4 / 6 kW

SINCE 1941  
**KETKO**™  
Engineered to perfection



**M**  
Mains ON indicator



**I**  
Insulation Energy Saver



**PSB**  
Power Safety Buzzer

**Also Available**

**6 Bar HG**

**High Pressure**

(Suitable for High Rise  
and Pressure Pump)

Tested at 10 Bar



6 / 10 / 15 / 25 / 35 / 50 Litres 230Volts / 1 Phase 3 / 4 / 6 kW

## PLACEMENTS

- Vertical
- Horizontal

## APPLICATIONS

- 1BHK/2BHK with single person using bathroom
- 1BHK/2BHK with multiple users in same bathroom in short span of time
- Bathrooms with low ceiling with small shower unit
- Bathrooms with independent children's bathrooms
- Heavy Gauge models for high rise apartments using pressure pumps
- Saloons/parlours
- Gym/health clubs
- Commercial kitchens, canteens, restaurants



### 10 BAR HIGH PRESSURE WITH SS 304 1.2 MM INNER TANK

10 BAR inner tank of stainless steel SS 304 ideal for hi-rise buildings and pressure pumps applications.



### REPLACABLE FUSIBLE PLUG

Double safety in case thermal cutout fails to operate thus preventing bursting of storage tank.

## OUTSTANDING FEATURES



### MULTI-FUNCTIONAL VALVE

4 way device that releases

- Excess pressure build-up
- Prevents back flow of water
- Prevents vacuum collapse of tank
- Drainage system



### RUST RESISTANT

Model with metal jacket outer body is rust resistant



### COPPER ELEMENT

High quality copper heater element for faster and better heat conduction



### UNIQUE HEATER PLATE

Helps in timely maintenance and cleaning of inner tank



### THERMOSTAT & THERMAL CUT-OUT

Auto power cut-off is set at 60°C while a snap action non-self resetting cut-out automatically trips if the temperature exceeds 90°C. (In digi models thermostat is digital)



### M

Mains ON indicator



### I

Insulation Energy Saver



### PSB

Power Safety Buzzer



### FUSIBLE PLUG

Double safety in case thermal cutout fails to operate



### 8.5 BAR TEST PRESSURE, WORKING PRESSURE 3 BAR

The inner tank is built sturdily with highest quality stainless steel SS 304 grade.



### 10 BAR TEST PRESSURE WORKING PRESSURE OF 6 BAR WITH PRESSURE PUMP

Ideal for pressure pump applications.



### DIGITAL TEMPERATURE INDICATOR AND CONTROLLER

Only in digi models

## SPECIFICATIONS

Models	KETKO <i>magnus</i> ™ Storage					
Water volume capacity in litres	6	10	15	25	35	50
kWatt Power	3 / 4 / 6 kW					
Voltage / frequency	230 Volts / 50Hz AC only					
Working pressure	10Bar Test Pressure and 6Bar Working Pressure / STD 8.5Bar Test Pressure and 3Bar Operating Pressure					
Inlet / outlet connection	1/2" BSP					
Inner tank	Stainless steel 304					
Digital temperature selection	35°C to 65°C (available in digi models only)					
Pre-set thermostat	Stem type thermostat is factory preset at 65°C for non-digi models					
Product Dimensions (mm)	6 L	10 L	15 L	25 L	35 L	50L
Diameter x Height	254 x 550	305 x 550	305 x 650	305 x 840	356 x 780 / 305 x 915	356 x 965 / 305 x 1290

All specifications are subject to change without prior notice. Models are continuously getting upgraded. The company assumes no responsibility and disclaims all liability for damages resulting from use of this information or any other errors or omissions.



ELECTRIC | GAS | SOLAR  
WATER HEATERS

CIN: U31200MH1990PTCO58167

**Ketko San Pvt. Ltd.** An ISO 9001: 2015 Certified Company

**Regd. Office:** 307, Sejal Bhuvan, Nana Chowk, Mumbai - 400 007, India.

**Manufacturing Unit:** Lonavala, Pune - 410401, Maharashtra, India .

**E-mail:** info@ketko.in **Website :** www.ketko.in

**Customer Care:** +91 88798 64422 / 82914 44974 **Whatsapp:** 9029326600

DEALER